

For immediate release

Editorial Contact:

Laurie Gibbons
Phone 860-379-9172
laurie.gibbons@permabond.com

Technical Contact

Manny Dias
Phone 732-868-1372
manny.dias@permabond.com

Permabond LH056 Added to FGG/BM/CZ™ System Compatible Program

SOMERSET, NJ – Permabond® Engineering Adhesives announces that its pipe sealant LH056 is chemically compatible with [FlowGuard Gold®](#), [BlazeMaster®](#) and [Corzan®](#) CPVC piping systems and has been added to the [FGG/BM/CZ™ System Compatible Program](#). Permabond LH056 is a pipe sealant designed for use in sealing metal pipes in sprinkler systems which may also contain CPVC piping. Permabond LH056 prevents leaks even on pipes that are not completely seated. Permabond LH056 forms an instant seal and once fully cured the seal will generally surpass the burst rating of the pipe.

Permabond Pipe Sealants use anaerobic technology to prevent leaks in sprinkler systems. Used in fabrication and installation, Permabond Pipe Sealants replace pipe dope and sealing tapes with a complete and reliable seal even if pipes are not completely seated. They prevent corrosion and lock against vibration loosening. They do not remain a paste, like pipe dope, but cure to a solid plastic seal. Cure is initiated by the presence of metal and the absence of air.

FGG/BM/CZ™, FlowGuard Gold®, BlazeMaster® and Corzan® are registered trademarks of The Lubrizol Corporation.

Permabond is a global, ISO 9001:2000 certified manufacturer of engineering adhesives and sealants for manufacturing, assembly, repair, and maintenance. Permabond manufactures cyanoacrylates (instant adhesives), anaerobics (for threadlocking, retaining, gasketing and pipe sealing), structural adhesives (one or two component epoxies and toughened acrylic adhesives), and UV - visible curable adhesives. Permabond custom formulates for unique requirements. Permabond products are sold worldwide through authorized distributors. For information

"Our Science . . . Your Success"

Help Line: 800.640.7599 • Customer Service: 800.714.0170 • Fax: 800.334.3219 • Sales Support: 610.323.6952

Headquarters: 223 Churchill Ave, Somerset, NJ 08873 • *Telephone:* 732.868.1372 • *Fax:* 732.868.0267

Warehouse: 14 Robinson Street, Pottstown, PA 19464 • *Telephone:* 610.323.5003 • *Fax:* 610.323.6980

www.permabond.com

